

Household grease under the sink series "Arctic".

Grease trap series "Arctic", made of heat-resistant plastic.



Due to the physicochemical properties of the polymer, the temperature range of the grease separator has increased from -40 C to +80 C. The grease trap is installed under the sink or next to it, as well as in pits or pits on the street.

Thanks to the standard sockets or additional couplings, different ways of connection of the grease trap to the sewerage system are possible, either through corrugated pipes or PVC hoses, or by standard sewer fittings (diameter 50mm).

This model of grease collector can now, undoubtedly, be placed in street wells or small pits. At the same time, a small volume (60 liters) and the

price remain the same as for the grease trap "under the sink"!

The grease trap in this version fully meets all the norms and requirements of the water and environmental services.

Also the production of this model with filter packages - "Arktika" -F

The grease trap "Arctic" is a solution of "fat" issues for both the water canal and sanitary station services, and for the owners of all kinds of street cafes, IAFs and tents with shawarma, pies and chebureks!

For today, all these fast-food points drain their fats at best into the nearest sewers, although this can often be ordinary stormwater, from where all this fatty film gets directly into the pipelines and naturally clogs them.

Fat collectors "Arctic" are not afraid of either great frosts or heat. The plastic used in their production is not afraid of sunlight, since it passes UV (ultra-violet) stabilization and is designed for long-term operation under the most extreme conditions.

Fat collectors "Arctic" can be installed for the duration of the operation near the MAF, and drained into the drain by using a flexible PVC hose or pipes with a diameter of 50 mm.

Main characteristics:

Length: 440mm; Width:390mm; Height:410mm. (540x440x410 - mounting)

Entrance height:340mm; Output height:300mm.

Productivity - 0.5 m³ / h (0,145 l / s)

Rated peak discharge - 35L

Due to the high partition in the grease trap, it can also be used as a gypsum trap or a sand catcher under the sink.

The company "POLIMERKOMPLEKT" produces standard fat separators up to 4000 liters.

You can get acquainted with the full assortment of our grease traps by downloading our prices or visiting our online store.

